


# Trhací s plochou hlavou

Cu/St

dřík - měď  
trn - ocel zinkovaná



d mm	vrtání mm	L mm	s mm	D mm	k mm	tah N	střih N
3,0	3,1	5	1,0 - 2,5	6,5	0,8	930	635
		6	1,5 - 3,0				
		7	3,0 - 4,0				
		9	4,0 - 6,0				
		11	6,0 - 8,0				
		12	8,0 - 9,0				
		14	9,0 - 11,0				
		16	11,0 - 13,0				
3,2	3,3	4,5	- 1,3	6,0	0,8	930	635
		6	1,5 - 3,0	6,0	0,8	930	635
		7	3,0 - 4,0	6,4	1,0	1200	800
		9	4,0 - 6,0	6,5	0,8	1130	880
3,4	3,5	6	1,5 - 2,5	6,7	1,0	1300	1000
		7	3,0 - 4,0				
		9	4,0 - 5,5				
		11	6,0 - 7,5				
		14	8,0 - 10,0				
		16	11,0 - 12,0				
		18	13,0 - 15,0				
		20	15,0 - 17,0				
22	17,0 - 19,0						

d mm	vrtání mm	L mm	s mm	D mm	k mm	tah N	střih N
4,0	4,1	6	1,0 - 2,5	8,0	1,0	2010	1270
		7	2,5 - 3,5				
		8	2,5 - 4,5				
		9	3,5 - 5,5				
		11	5,5 - 7,5				
		12	6,5 - 8,5				
		14	8,5 - 10,5				
		16	1,5 - 12,5				
		18	12,5 - 14,0				
		20	14,0 - 16,0				
		25	16,5 - 21,5				
30	21,5 - 26,5						
4,8	5,0	7	1,0 - 3,5	9,5	1,1	2780	1950
		8	2,0 - 4,0				
		10	4,0 - 6,0				
		11	5,0 - 7,0				
		12	6,5 - 8,5				
		14	8,0 - 10,0				
		16	9,0 - 12,0				
		18	12,0 - 14,0				
		20	14,0 - 16,0				
		25	16,0 - 20,0				
		28	20,0 - 23,0				
30	23,0 - 25,0						